



HRZ8715F is a recessed linear profile made of extruded aluminum housing powder-coated with a protective white sand texture with a matte finish.

This linear LED luminaire is designed to produce a uniform distribution of diffused light in drywall platforms. HRZ8715F can be used to create a floor-wash or ceiling-wash feel depending on the level it is installed within the wall and comes in variable lengths up to 18 feet.*

Horizon series can be conveniently controlled with multi-zone wall touch keypad and smart mobile app options. SPK8715F is a perfect fit for use in residential and commercial spaces for wet and dry applications to produce ambient or decorative illumination.

EnoLight lighting solutions are designed and manufactured in Canada to the highest industry standards with 5 years warranty.

SPECIFICATIONS

ELECTRICAL

WATTAGE

2.4W/ft, 5W/ft
24 Volt DC input

OPERATING TEMP

-31°F to +113°F
-35°C to +45°C

CERTIFICATION

U.S./Canada UL approved
Type IC Recessed



CONTROL

DIMMING MODE

Class 2 Flicker-Free
Dimmable, DMX Tunable,
Non-Dimmable

WALL KEYPAD

Dimmer switch, Multi-zone
DMX dim and tuning touch
key with smart mobile App

PHYSICAL

DIMENSION

3.42 in x 0.64 in, 87x16mm
Up to 18ft length, 0.35 lb/ft

FINISH

White matte powder coat with
sand texture finish *

FIELD

Recessed in drywall close
to ceiling or flooe



LIGHT

LED TYPE

Single white, Tunable white,
Circadian Rhythm

EFFICACY

100 Lm/W, Max 400 Lm/ft *

LIFESPAN

50,000 hours

WARRANTY

5 years warranty

HRZ8715F	8F	200	SA	30K	JT	F5
Indirect Hallway Linear LED Light	1FT-18FT 1' to 18' Custom length up to 18'	200 200lm/ft 2.4W/ft 400 400lm/ft 5W/ft	SA Silver Anodized BM Black Matte WM White Matte	27K 2700K Incandescent 90CRI 30K 3000K Warm Halogen 90CRI 35K 3500K Neutral White 90CRI 40K 4000K Cool White 90CRI 50K 5000K Daylight White 90CRI 27T 2700K-6500 Tunable 90CRI CR Circadian Rhythm 97R9 98CRI	JT Triac Phase Dimming JX DMX Multi-Channel JN Non-Dimmable JD DALI Dimmable JO 0-10V Dimmable	F2 Dry Field F5 Wet Field

* Available for custom applications. Visit enolight.com or contact sales@enolight.com for further details.

Disclaimer: The actual product may vary from the images shown. Due to differences in monitors, colours of products may also appear different to those shown. Specification and illustrations provided for each product is to be used as a general guide only. Copyright © EnoLight Ltd. All Rights Reserved.